

## Low-cost Process Indicator TI08

- ◆ **Lowest cost**
- ◆ **6 DIN cases - up to 1/32 DIN**
- ◆ **4-digit bright LED indication**
- ◆ **Universal linear input**
- ◆ **Up to 2 alarm relays available with pulsed output**
- ◆ **Fully programmable parameters**

TI08 is a cheap programmable process indicator available in 6 DIN cases and designed for wide range of display applications with/without relay alarm. Equipped with a bright 4-digit LED display, this model is especially suitable for measuring and controlling various technological values from -1999 to 9999 with resolution of up to 6000 points. The device may be equipped with up to 2 programmable relays providing ON/OFF control/alarm with or without pulse mode. TI08 accepts various linear input voltage or current signals. The display limits, decimal point position, measurement offset value as well as many other parameters are fully programmable. Thanks to its excellent price-to-performance ratio, TI08 is an exceptionally widely applicable device.



### Technical specifications

Input		<i>(programmable)</i>
<b>Linear voltage 0...10 V</b>	-1999...9999, programmable	
<b>Linear voltage 0...5 V <sup>(1)</sup></b>	-1999...9999, programmable	
<b>Linear current 0(4)...20 mA</b>	-1999...9999, programmable	
<b>Custom linear <i>(option)</i></b>	-1999...9999, programmable	
<b>Two-wire external transmitter</b>	4...20 mA <sup>(2)</sup>	
<b>Decimal point selection</b>	programmable	
Outputs		<i>(up to 2 relay outputs <sup>(3)</sup>)</i>
<b>Relay electromechanical</b>	5A/250V w/ NO/NC <sup>(4)</sup> contact	
<b>Solid state relay <sup>(7)</sup></b>	1A/250VAC <sup>(5)</sup>	
<b>MOS gate <sup>(7)</sup></b>	0.1A/60V, optically isolated	
<b>Output for external SSR</b>	5...24 V, 30 mA	
<b>Control algorithm</b>	ON/OFF, pulse mode	
<b>Alarms</b>	programmable	
Accuracy		
<b>Measurement error</b>	0.3% from span	
<b>Temperature drift</b>	0.02% from span for 1 °C	
Operating conditions		
<b>Ambient temperature</b>	-10...65 °C	
<b>Ambient humidity</b>	0...85 %RH	

Power supply						
<b>Mains supply voltage <sup>(1)</sup></b>		230 VAC or 115 VAC				
<b>SMPS voltage <sup>(1)</sup></b>		90...250 V				
<b>Isolated low voltage</b>		12...24 V or 24 VAC <sup>(1)</sup>				
<b>Non-isolated low voltage</b>		12...24 V				
<b>External mains transformer <sup>(6)</sup></b>		9(12) VAC				
<b>Consumption</b>		max. 1.5 VA				
Indication and controls						
<b>Digital display</b>		4 LED indicators				
<b>LEDs</b>		2 LEDs for output state				
<b>Keyboard</b>		2 membrane keys, lockable				
Design and materials		'B'	'H' / 'V'	'S'	'L'	'M'
<b>Front dimensions [mm]</b>		96x96	96x48	48x48	72x36	48x24
<b>Mounting</b>		panel	panel	panel	panel	panel
<b>Panel cutout [mm]</b>		90x90	90x42	45x45	71x29	46x22
<b>Mounting depth [mm]</b>		98	98	100	56	42
<b>Display digit height [mm]</b>		20	14 / 9	10	14	9
<b>Maximum weight [g]</b>		350	250	200	150	30
<b>Protection, front/terminals</b>		IP54/20	IP54/20	IP54/20	IP54/20	IP54/20
<b>Increased front IP <i>(option)</i></b>		IP65	IP65	-	IP65	-
<b>Case material</b>		plastic	plastic	plastic	plastic	plastic
<b>Wiring (terminals)</b>		plug-in	plug-in	screw	screw	screw

<sup>(1)</sup> Not available for case 'M'  
<sup>(2)</sup> Provides loop supply voltage - 24 VDC (only w/ isolated power supply)  
<sup>(3)</sup> Only one for case 'M'  
<sup>(4)</sup> For case 'S' 2<sup>nd</sup> relay is NO; for case 'L' both relays are NO; for case 'M' relay is NO  
<sup>(5)</sup> 0.2A/250VAC for cases 'L' and 'M'  
<sup>(6)</sup> Available only for case 'M'. Transformer is ordered separately.  
<sup>(7)</sup> Ask for availability!

### Ordering code TI08 - G0.G1.G5G5 - #1.#2

Code	Feature or option	Code values
<b>G0</b>	Case (front size)	<b>B</b> - 96x96 mm, <b>H</b> - 96x48 mm, <b>V</b> - 48x96 mm, <b>S</b> - 48x48 mm, <b>L</b> - 72x36 mm, <b>M</b> - 48x24 mm
<b>G1</b>	Power supply	<b>A</b> - 230 VAC <sup>(1)</sup> , <b>B</b> - 115 VAC <sup>(1)</sup> , <b>C</b> - 90...250 V <sup>(1)</sup> , <b>E</b> - 9(12) VAC w/ external transformer <sup>(6)</sup> , <b>P</b> - 12...24 V, non-isolated, <b>Q</b> - 12...24 V, isolated, <b>R</b> - 24 VAC <sup>(1)</sup>
<b>G5</b>	Relay output <sup>(3)</sup>	<b>X</b> - none, <b>C</b> - relay NO/NC <sup>(4)</sup> , <b>D</b> - SSR <sup>(7)</sup> , <b>J</b> - for external SSR, <b>M</b> - isolated MOS gate <sup>(7)</sup>
<b>#1</b>	Increased front protection	<b>X</b> - none, <b>P</b> - IP65 front protection <sup>(1,8)</sup>
<b>#2</b>	Customer specified input signal	<b>X</b> - none, <b>Z</b> - custom linear signal (specify!)

<sup>(8)</sup> Not available for case 'S'