DigippeSulfuric Acid (H₂SO₄) Digestion & Distillation Systems

| | Nitrogen | . / |
|--|----------|------|
| | | RoHS |
| | Many N | |





sales@scpscience.com • www.scpscience.com

Sample Digestions

The *Digi*PREP HT series of block digestion systems offers the latest in graphite block technology in four different packages. Graphite blocks are coated with silicon carbide (SiC) which resists aggressive, corrosive attack for guaranteed long life in harsh laboratory environments. The systems have a temperature range from ambient to 450°C and require either a *Digi*PREP Touch Screen or KeyPad controller.

Digestion Made Easy...

The *Digi*PREP HT series* is available in four models - two models employing 100 ml tubes and two models with 250 ml tubes. An all-Teflon® manifold, with its unique Teflon® tube adaptors, removes corrosive acid fumes while promoting gentle refluxing. With its two-tier, dual zone tube rack, benchtop space is reduced by 50% allowing more room for other lab instruments. *Digi*PREP HT systems are ideal for Kjeldahl/TKN, WEEE RoHS, and for any application using sulfuric acid (H₂SO₄).



DigiPREP HT - 250 20 - sample capacity (Catalog No. 010-520-222)

Build a Complete System...

| | DigiPRE | P HT 100 | DigiPREP HT 250 | | |
|---------------------|----------------------|--------------------------|----------------------|-------------------------|--|
| Information | 40 - Position | 10 - Position | 20 - Position | 10 - position | |
| Catalog Number | 010-520-202 | 010-520-235 | 010-520-222 | 010-520-245 | |
| Capacity | 40 samples | 10 samples | 20 samples | 10 samples | |
| Tube Capacity (Max) | 115 ml | 115 ml | 300 ml | 300 ml | |
| Nominal Volume | 100 ml | 100 ml | 250 ml | 250 ml | |
| Temperature (Max) | 450 °C | 450 °C | 450 °C | 450 °C | |
| Voltage (Volts) | 230 | 230 | 230 | 230 | |
| Size (in) | 17 W x 17.5 D x 27 H | 17. 75 W x 12.5 D x 27 H | 17 W x 17.5 D x 27 H | 17.75 W x 12.5 D x 27 H | |

Total Control at Your Fingertips...

Color Touch Screen Controller (010-500-250)

The Touch Screen controller is recommended for all multi-step, multi-temperature digestions such as Kjeldahl and RoHS digestions.

Includes all of the KeyPad controller features, plus:

- Store up to 12 custom methods
- Each method offers 6 programmable steps of
 - Time-to-temperature
 - Time-at-temperature
- View a graphical representation of the heating profile in real-time



- Includes built-in safety features and calibration parameters:
 - Calibration of controller; up to 5 points
- Built-in, selectable language sets:

Chinese Italian
Dutch Japanese
English Korean
French Portuguese
German Spanish

KeyPad controller (010-500-220)

Inputting operating parameters is made easy with the DigiPREP KeyPad controller. Features include:

- programmable:
 - timer with shutdown option
 - temperature set-point to 0.1°C
 - programmable alarm for end of segment



- displays block temperature
- displays actual time remaining in sequence
- useable in five different languages
- utilizes safety messages to prevent failure
- calibration of controller; up to 5 points

^{*} System(s) require the use of a controller

Distillation Systems

<code>DigiPREP</code> distillation systems range from manual to fully automatic. Systems are programmed and operated using a single, turn-and-press knob. All systems can be used for the steam distillation of Kjeldahl ammonia solutions. In the Kjeldahl application, the additions of NaOH, $\rm H_2O$, and $\rm H_3BO_3$ may be automated. Samples can be distilled in 3 to 5 mintues. Variable steam power from 40% to 99% is offered for alcohol and phenol analysis in most models. Automatic drainage of hot sample waste provides safety and convenience.

An instrument is available to suit every budget.

Please review the chart below to determine model of choice.



DigiPREP Distillation System
Model - 300
(Catalog No. 010-035-003)

DigiPREP Steam Distillation Systems

| CEATURES | DigiPREP Distillation System Model | | | | |
|--|------------------------------------|-----------------|-----------------|-----------------|---------------|
| FEATURES | 100 | 200 | 300 | 400 | 500 |
| CATALOG NUMBMER | 010-035-001 | 010-035-002 | 010-035-003 | 010-035-004 | 010-035-005 |
| Automatic Addition of H ₂ O | | • | | • | |
| Automatic Addition of NaOH | • | • | • | • | • |
| Automatic Addition of H ₃ BO ₃ | | | | • | • |
| Programmable Reaction Time | • | • | • | • | • |
| Programmable Distillation Time | • | • | • | • | • |
| Automatic Steam Generation | • | • | • | • | • |
| Variable Steam Generating capacity (40% -100%) | • | • | • | • | |
| Automatic Removal of Sample Waste by Suction | | | • | • | • |
| Number of Programs | 1 | 1 | 10 | 99 | 99 |
| Display Language Can Be Chosen by the User | • | • | • | • | • |
| Visual Error Reports | • | • | • | • | • |
| Acoustic Error Reports | • | • | • | • | • |
| Standby Operation Between Distillations | • | • | • | • | • |
| Level Monitoring for the Set of Canisters | • | • | • | • | • |
| Connection for Titration Unit | | | | | • |
| Voltage (volts) | 230 | 230 | 230 | 230 | 230 |
| Dimensions (W x H x D in mm) | 410 x 675 x 410 | 410 x 675 x 410 | 410 x 675 x 410 | 410 x 675 x 410 | 410 x 675 x 4 |
| Weight (kg) | 34 | 34 | 35 | 35 | 36 |

^{*} Built-in selectable language sets in English, French and German

Accessories

Dual Probe (010-520-310)

For applications where temperature must be verified for auditing purposes. One probe is used for control while the second probe can be connected to a calibrated readout.

| | DigiPREP HT 100 | | DigiPREP HT 250 | |
|--------------------------------|-----------------|---------------|-----------------|---------------|
| Information | 40 - Position | 10 - Position | 20 - Position | 10 - position |
| DigiPREP HT with Dual Probe | 010-520-402 | 010-520-435 | 010-520-422 | 010-520-445 |



Glass Ball Condenser (010-520-312)

Vapor rising into the glass condenser is efficiently cooled onto the glass fingertips to flow back into the distillation tube for efficient refluxing. Refluxing also prevents the sample from going to dryness. Condensers can be used when the Teflon Manifold is not in use.



Universal Fume Scrubber (010-520-160)

Removes and neutralizes acid fumes during the digestion. The system involves a series of bottles; condenser, neutralizing bottle and acid waste collecting. May be used with all *Digi***PREP HT** digestion models. System works best with a chiller, not included.



pH Titrator (010-035-050)

Accurate dosing technology and high-precision glass cylinders ensure correct titration results. An easy to read display shows the quantity of the titrant used; delivers with 0.01 ml accuracy. May be connected to *DigiPREP* 500 distillation system to automate the final stage of Kjeldahl analysis.



Service Department

Our friendly Service Department will gladly assist you with technical questions pertaining to *DigiPREP* products. With over 30 years in servicing instruments, our staff will review and resolve issues quickly.

Website: www.scpscience.com • **Email:** sales@scpscience.com

U.S.A. Tel.: (800) 361-6820 Fax: (800) 253-5549 Canada / International Tel.: (800) 361-6820 / +1 (514) 457-0701 Fax: (800) 253-5549 / +1 (514) 457-4499 Europe Tel.: +33 (0) 1 69 18 71 17 Fax: +33 (0) 1 60 92 05 67

China

Tel.: +86 (10) 58032301 Fax: +86 (10) 58032302